HARD Servos



HARD6810 - HS3004 Standard Servo

The HARD HS3004 is a standard **ball raced** servo for any RC application.

Specifications:

Dimension: 40.4 x 36 x 19.8mm

Weight: 37g

Input voltage: 4.8 to 6V

Speed: 0.23s @ 4.8V / 0.19s @ 6V

Torque: 3.2kg-cm @ 4.8V / 4.1kg-cm @ 6V

Features: Ball Bearing



HARD6823 - HS3307 HT MG Servo

The HARD HS3307 is a **ball raced High Torque** servo with **Metal Gears**, designed for many RC applications which require high torque purposes.

Specifications:

Dimension: 40.7 x 39.4 x 19.6mm

Weight: 49g

Input voltage: 4.8 to 6V

Speed: 0.22s @ 4.8V / 0.19s @ 6V

Torque: 8.6kg-cm @ 4.8V / 10.5kg-cm @ 6V Features: 2 Ball Bearings / Metal Gear



HRC Switzerland

HRC Distribution GmbH Hofackerstrasse 14 CH-4132 Muttenz Switzerland

Phone: +41 61 461 53 44 Fax: +41 61 544 74 06 HRC Europe

Hartweg R/C
Pestalozzistrasse 54
DE-79540 Loerrach-Stetten
Germany

Phone: +49 76 219 359 937 Fax: +49 76 215 879 411

Visit our website: www.hrcdistribution.com

